



Total creepage [mm]	317
Air-distance [mm]	165
Dry-flashover [kV]	85
Wet-flashover [kV]	50
Drywithstand [kV]	50
Wetwithstand [kV]	38
Impulse voltage [kV]	95

$U_N$ [kV]	8,5	PARALLEL ELEM.	2
$Q_N$ [kvar]	100	SERIES GROUPS	4
$C_N$ [ $\mu$ F]	4,4 (-5/+10%)	WEIGHT [kg]	20
$f_N$ [Hz]	50,0	LIQUID CAP. [kg]	5,7
$I_N$ [A]	11,8	STANDARD	IEC 60871-1/05
BIL [kV]	38/95	INT. FUSES	NO
TEMP. CAT.	-40/C	SIDE BRACKETS	YES
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES
DISCHARGE	75 V/600 s (12 MOhm)		

CONNECTION	I
CASE MATERIAL	Stainless steel
DIMENSIONS:	
A [mm]	145
B [mm]	250
C [mm]	522
D [mm]	100

DRAWING No.:	4J8726A	TYPE:	CUEFS 23-8,5/100
--------------	---------	-------	------------------

DRAWN:	Stehlík
CHECKED:	Ing.Koryták
DATE:	10.7.2009

	<b>ZEZ SILKO s.r.o.</b> Žamberk CZECH REPUBLIC	ZEZ SILKO s.r.o. Pod černým lesem 683 564 22 Žamberk Czech Republic	tel.: +420 465 673 111 fax.: +420 465 612 319 e-mail: <a href="mailto:zez@zez-silko.cz">zez@zez-silko.cz</a> http:// <a href="http://www.zez-silko.cz">www.zez-silko.cz</a>
--	--	--	--